

Access Controls / Hikvision / Standalone

DS-K1T320MFWX

HIKVISION



Features

- Hikvision
- Autonomous biometric reader for access and presence control
- Identification by MF-card, fingerprint, facial recognition, password and/or combinations
- Display 2.4" TFT color display
- Capacity of 500 faces, 1.000 cards, 1.000 fingerprints and 100.000 records
- TCP/IP, WiFi and USB connection
- Integrated controller (door sensor, push button and relay)
- White LED camera with anti-spoofing technology
- Remote openings from Hik-Connect
- Compatible with software iVMS-4200

Specifications

Brand	Hikvision
Model	DS-K1T320MFWX
Operating system	Linux
Capacity	Up to 500 faces, 1.000 fingerprints and 1.000 cards/passwords
Records	100.000 registers
Identification modes	Facial recognition, fingerprint, card, PIN and/or combinations
Proximity card	MF (13.56 MHz)
Screen	2.4" Color TFT LCD
Screen resolution	320 x 240
Camera	2 Mpx with white LED
Facial recognition verification time	< 0.2 sec
Facial recognition accuracy	> 99%
Facial recognition distance	0.3 m to 1.5 m
Fingerprint verification time	< 1 sec
Communication	TCP/IP, WiFi and USB
Integrated controller	Door sensor, pushbutton and relay
Alarms	Tamper
Software	iVMS-4200 / iVMS-4200 AC
Mobile application	Hik-Connect
Power supply	DC 12 V / 500 mA máx.
Degree of protection	Valid for interior
Temp. operation	-10º C ~ +55º C
Dimensions	130 (W) x 150 (H) x 24.7 (D) mm
Weight	220 g